












Produktbezeichnung Dénomination des produits	Lieferform Mode de livraison			Dicke Epaisseur
	Einheit Unité	Menge/Pak Quantité/Paq	Fläche Surface	
<b>XPS Drain SF</b> Extrudierte Polystyrolwärmesdämmplatte mit Drainage-Schicht Rohdichte: > 30 kg/m <sup>3</sup> Format: 125 x 60 cm Labda: 0,035 – 0,036 W/mK  Panneau d'isolation thermique en polystyrène extrudé avec couche de drainage Masse volumique: > 30 kg/m <sup>3</sup> Format: 125 x 60 cm Labda: 0,035 – 0,036 W/mK		7	5.25 m <sup>2</sup>	50 mm
		6	4.5 m <sup>2</sup>	60 mm
		5	3.75 m <sup>2</sup>	80 mm
		4	3 m <sup>2</sup>	100 mm
		3	2.25 m <sup>2</sup>	120 mm
		3	2.25 m <sup>2</sup>	140 mm
		3	2.25 m <sup>2</sup>	160 mm
		2	1.5 m <sup>2</sup>	180 mm
		2	1.5 m <sup>2</sup>	200 mm
		2	1.5 m <sup>2</sup>	220 mm
		2	1.5 m <sup>2</sup>	240 mm